

STONE LOOK

Stony



MARAZZI



Stony

Stony is the new porcelain stoneware collection inspired by a limestone, characterized by small details and delicate veins that bring naturalness and depth to surfaces. With its essential and refined look, the collection interprets an authentic material in a modern key, offering elegance and design versatility.

Available in four colors – the warm Ivory and Beige and the cool Grey and Greige – Stony comes in sizes 60x120, 80x80, 60x60, and 30x60 with a Natural R9 surface, while the 60x120 and 60x60 sizes are also available in Outdoor R11 C version, for continuous In&Out surfaces.

The extra-thickness version Stony20, in 60x60 format, enriches the collection, allowing outdoor installation, dry laying on grass, sand, gravel, or on driveways.

MQJU Stony Ice Rt 60x60cm
MQJJ Stony Ice Rt 60x120cm
MQGL Arcadia Calacatta Ivory Rt 60x120cm







Stony Index

MQJU Stony Ice Rt 60x60cm
MQJJ Stony Ice Rt 60x120cm
MQGL Arcadia Calacatta Ivory Rt 60x120cm

Stony

- Porcelain Stoneware




Beige

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
30x60cm	Natural	MQJF	Stony Beige Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		7	1,26	22,46	48	60,48	1.078,07
60x120cm	Structured Surface	MQJP	Stony Beige Strutturato	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R11C	> 0.40	Class 3	36+ Both Sliders		>= 0.42	G		2	1,44	27,00	36	51,84	972,06
60x60cm	Natural	MQJT	Stony Beige Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		3	1,08	19,73	48	51,84	946,85
60x60cm	Structured Surface	MQJZ	Stony Beige Strutturato	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R11C	> 0.40	Class 3	36+ Both Sliders		>= 0.42	G		3	1,08	20,00	48	51,84	960,00
60x120cm	Natural	MQJM	Stony Beige Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		2	1,44	27,32	36	51,84	983,68
80x80cm	Natural	MQKE	Stony Beige Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		2	1,28	22,79	48	61,44	1.093,82




Grey

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
30x60cm	Natural	MQJE	Stony Grey Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		7	1,26	22,47	48	60,48	1.078,46
60x120cm	Structured Surface	MQJR	Stony Grey Strutturato	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R11C	> 0.40	Class 3	36+ Both Sliders		>= 0.42	G		2	1,44	27,00	36	51,84	972,06
60x60cm	Natural	MQJV	Stony Grey Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		3	1,08	19,69	48	51,84	945,30
60x60cm	Structured Surface	MQKC	Stony Grey Strutturato	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R11C	> 0.40	Class 3	36+ Both Sliders		>= 0.42	G		3	1,08	20,00	48	51,84	960,00
60x120cm	Natural	MQJL	Stony Grey Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		2	1,44	27,62	36	51,84	994,44
80x80cm	Natural	MQKF	Stony Grey Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		2	1,28	22,69	48	61,44	1.088,98



Ice

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
30x60cm	Natural	MQJG	Stony Ice Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		7	1,26	22,52	48	60,48	1.080,97
60x120cm	Structured Surface	MQJQ	Stony Ice Strutturato	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R11C	> 0.40	Class 3	36+ Both Sliders		>= 0.42	G		2	1,44	27,00	36	51,84	972,06
60x60cm	Natural	MQJU	Stony Ice Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		3	1,08	19,86	48	51,84	953,12
60x60cm	Structured Surface	MQJY	Stony Ice Strutturato	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R11C	> 0.40	Class 3	36+ Both Sliders		>= 0.42	G		3	1,08	20,00	48	51,84	960,00
60x120cm	Natural	MQJJ	Stony Ice Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		2	1,44	28,30	36	51,84	1.018,87
80x80cm	Natural	MQKG	Stony Ice Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		2	1,28	22,77	48	61,44	1.093,04



Ivory

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
30x60cm	Natural	MQJH	Stony Ivory Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		7	1,26	22,42	48	60,48	1.075,97
60x120cm	Structured Surface	MQJN	Stony Ivory Strutturato	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R11C	> 0.40	Class 3	36+ Both Sliders		>= 0.42	G		2	1,44	26,67	36	51,84	960,18
60x60cm	Natural	MQJS	Stony Ivory Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		3	1,08	19,82	48	51,84	951,19
60x60cm	Structured Surface	MQK0	Stony Ivory Strutturato	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R11C	> 0.40	Class 3	36+ Both Sliders		>= 0.42	G		3	1,08	20,00	48	51,84	960,00
60x120cm	Natural	MQJK	Stony Ivory Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		2	1,44	27,36	36	51,84	984,99
80x80cm	Natural	MQKD	Stony Ivory Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall		R9	> 0.40	Class 1			>= 0.42	G		2	1,28	22,60	48	61,44	1.084,94

Legenda

Destinazioni d'uso

D
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

G
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

Variazioni cromatiche

V0
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

V3
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni



ISO 14001



LEED Credits



CE 009MRZI



ISO 9001



FDES



UKCA 001MRZUK



Green Building Council



Declare



UKCA 009MRZUK



GPP



HPD



SASO



EPD Italy



CAM Sassuolo



ISO 17889-1



CE 001MRZI

© Copyright by Marazzi Group S.r.l., 2023.
All rights reserved, Marazzi Group Srl a Socio Unico
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



MARAZZI